

IN THE CLAIMS:

1. **(Currently Amended)** A safety coupling arrangement apparatus comprising

a coupling part that ~~can be adapted for fixed co-action~~coaction with a shaft or axle that ~~functions to transfer~~for accepting torque and rotary movement ~~to said safety coupling, and~~

a ~~further~~second coupling part which ~~is adapted for fixed co-action~~coaction with a shaft axle ~~to transfer~~for delivering torque and rotational movement ~~from the safety coupling, and~~
further including

a safety unit, ~~wherein said safety unit is adapted to take one of two~~
settings, a first setting in which torque and rotary movement ~~can be~~is
transferred between said ~~two~~first and second coupling parts and a second
setting in which no torque and rotational movement ~~can be~~is transferred
between said ~~two~~first and second coupling parts, ~~wherein said safety unit~~
~~includes a~~including an expandable subpart ~~or a body that can take said~~
first setting as a result of an expansion caused by applying pressure to a
cavity within the safety unit and enclosing said pressure in said cavity,
and is able to take its second setting by evacuating said pressure from
said cavity, wherein ~~a~~one of said first coupling part ~~or a~~and said second
coupling part includes ~~an axially directed, or a generally axially-~~
~~directed~~[[,]] groove, ~~wherein said groove is adapted to be able to~~
~~surround~~which surrounds a pressure expandable subpart in said safety

unit and ~~the whole, or essentially the whole~~[[7]] of said cavity, and wherein said expandable subpart, when in its first setting, functions to allow torque to be transferred directly to said first coupling part or said second coupling part via two mutually opposing surface parts[[7]] which are frictionally active against opposing outer parts of the axially-directed groove, wherein said first coupling part includes two axially-directed projections each adapted for coaction with a respective groove in the second coupling part, and are shorter than said cavity, wherein the expandable part is formed as an end locking means, and said locking means provides two axially-directed edges.

2. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, wherein one of said ~~one or said other~~ first and second coupling partparts includes a collar which is ~~centred or essentially centred~~ centered with respect to said axially-directed groove.

3. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 2, wherein said collar is integrated with said one coupling part ~~or said other coupling part~~.

4. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 3, including an outer radial groove formed between a flange and said collar, said flange ~~belonging to~~ of ~~one of said first and second~~ ~~or the other~~ coupling partparts.

5. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 4, wherein a thin material section is formed in said one ~~or~~ of said

~~either~~first and second coupling ~~part~~parts between said outer radial groove and said axially-directed groove of said safety unit.

6. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 5, wherein said thin material section is elastically resilient.

7. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, wherein said safety unit is integrated with and constitutes said first coupling part or said second coupling part and includes a flange for fixed ~~co-action~~coaction with ~~the a~~ torque transferring shaft connected to the safety coupling.

8. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, including a pressure medium filling nipple, ~~such as oil,~~ which extends radially out from the safety unit and is positioned in connection with said ~~one~~first and second coupling ~~part or said other coupling~~ ~~part~~parts and its collar.

9. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 8, including a device~~[[7]]~~ which is fixed in relation to said collar, which ~~co-acts~~coacts with ~~or is able to co-act with~~ said filling nipple such that a small relative movement between said first coupling part and said second coupling part and said safety unit will cause the filling nipple to shear~~[[7]]~~ for a rapid evacuation of said pressure.

10. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, including a first ball bearing ring placed at the bottom of the

s
safety unit groove for ~~co-action~~coaction between said safety unit and said groove.

11. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 10, including a second ball bearing ring placed adjacent an opening of said safety unit groove for ~~co-action~~coaction between the safety unit and said groove.

12. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, wherein said generally axially-directed groove has a conical cross-sectional shape with ~~the~~a widest part facing towards an adjacent part.

13. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 12, wherein ~~the~~a cross-sectional shape of said subpart and its sections has a corresponding conical shape.

14. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 13, wherein said generally axially-directed groove and said corresponding sections have a stepped cross-sectional shape with ~~the~~a widest part facing towards an adjacent part.

15. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 1, wherein ~~the~~ free end portions of ~~the~~ material sections or ~~the~~ legs forming said axially-directed groove are coordinated with locking means provided there between and adapted to prevent any divergence of said free end portions when the safety unit, together with its associated subpart or body, takes its first and expanding setting.

16. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 15, wherein said first coupling part and said second coupling part are mutually adapted to include mutually overlapping and coordinated cylindrical subsections on a respective side of an axially-directed groove .

17. **(Canceled)**

18. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim ~~18~~16, wherein said edges are related peripherally to said first coupling part, and wherein said groove is formed peripherally in said second coupling part.

19. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 16, wherein said subsection is adapted for torque transmission via axially orientated and cylindrical outer sections.

20. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 19, wherein ~~the~~a length of said outer sections and a normal pressure dependent on the chosen expansion of the expandable subpart are adapted for a torque transfer of between 10 and 30% of the total torque transferred between said coupling parts.

21. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 20, wherein the chosen torque transfer is adapted to between 15 and 25%.

22. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 20, wherein the generally axially-directed groove has a length of more than 50% of the length of said expandable subpart.

23. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 22, wherein said length is adapted to be less than 80% of the axial length of said expandable subpart.
24. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 16, wherein said overlapping subsections have the same, or essentially the same~~[[,]]~~ radial thicknesses.
25. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 15, wherein with regard to the overlapping subsections, the outer subsection has a greater thickness than the inner.
26. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 15, wherein the first coupling part is formed to function as a locking means against expansion of the free end portions of the legs forming said groove in the second coupling part.
27. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 26, wherein the legs forming said groove have the same, or essentially the same~~[[,]]~~ material thickness.
28. **(Currently Amended)** The apparatus ~~An arrangement~~ according to Claim 27, wherein ~~the~~a radius difference between the mutually opposing cylindrical outer parts of the groove is smaller than, equal to or essentially equal to ~~the~~a total radial thickness of said free end portions or legs.